

## P - PS

### Radial piston pumps

Size 2 (Solid concept)  
 500 Bar - 700 Bar - 1000 Bar  
 0,565 to 12,06 cm<sup>3</sup>/rev

#### Applications:

- Cutting device
- Offshore applications
- Synchronisation units ( multiple P-port connections)
- Lifting systems
- Presses
- Aerospace

#### Design:

- High-strength aluminum body and piston-cover
- Modular concept (easy to replace piston assembly)
- Customized assembly possible
- Marine version = FPM seals + special coated external parts



#### Features:

- Light weight solid version
- High volumetric efficiency (up to 98%)
- Wide speed range (100 > 3000 rev/min)
- Optional drive-through shaft (second pump)
- 1 to 6 Pressure outputs possible (depending on n° pistons)
- Low pulsation, low noise level
- Self-priming and venting
- Offshore versions available (Marine version)


#### Technical data:

Hydraulic fluid	Mineral or synthetic oil according DIN 51524 (BIO, other on demand)
Viscosity range	10 to 220 mm <sup>2</sup> /s
Recommended oil	ISO VG 10 to 68 cSt (conf. DIN 51 519)
Filtration	According ISO/DIN 4406 17/15/12 (NAS 1638 class 6)
Fluid temperature range	-30 to +80°C (attention to the viscosity range)
Ambient temperature range	-40 to +60°C
Speed range	100 to 3000 rev/min
Direction of rotation	Bi-directional
Suction height	max 500mm
Operation pressure on suction port	-0,2 Bar to 0,5 Bar
Max pressure on output port	500 Bar, 700 Bar or 1000 Bar (depending on piston size and version)
Axial force on driving shaft	Not allowed
Radial force on driving shaft	On request
Port connections	Via fittings ISO 228/1 (BSP), other on demand)

Size 2 (Solid concept)  
 500 Bar - 700 Bar - 1000 Bar  
 0,565 to 12,06 cm<sup>3</sup>/rev



**Ordering Code:**



**Maximum pressures and displacements of the standard program:**

Size	Housing	Nb of Pistons	Pressure (bar) / displacement (cm <sup>3</sup> ) by piston diameter					
			Ø 6 mm	Ø 8 mm	Ø 9 mm	Ø 10 mm	Ø 12 mm	Ø 16 mm
2	P	2	700/0,565	700/1,05	700/1,28	700/1,58	700/2,26	500/4,02
		4	700/1,13	700/2,10	700/2,54	700/3,14	700/4,52	500/8,04
		6	700/1,70	700/3,02	700/3,82	700/4,71	700/6,79	500/12,06
	PS	2	1000/0,565	1000/1,00	1000/1,27			
		4	1000/1,13	1000/2,01	1000/2,54			
		6	1000/1,70	1000/3,02	1000/3,82			



HYDROSERV - Wimmerpumps

Ninovesteenweg 212 F - B 9320 Erembodegem

Tel: +32 (0)53 71 12 12

Email : [contact@wimmerpumps.com](mailto:contact@wimmerpumps.com)

[info@hydroserv.eu](mailto:info@hydroserv.eu)