

PW

Radial piston pumps

Size 3 (Solid concept)

500 Bar

16,50 to 33,19 cm³/rev

Applications:

- Production machinery
- Offshore applications
- Synchronisation units (multiple P-port connections)
- Lifting systems
- Presses

Design:

- High-strength aluminum body and piston-cover
- Modular concept (easy to replace piston assembly)
- Customized assembly possible
- Marine version = FPM seals + special coated external parts



Features:

- Solid version
- High volumetric efficiency (up to 98%)
- Wide speed range (100 > 1800 rev/min)
- Optional drive-through shaft (second pump)
- 1 to 6 Pressure outputs possible (depending on n° pistons)
- Low pulsation, low noise level
- Self-priming and venting
- Offshore versions available (Marine version)

Technical data:

Hydraulic fluid	Mineral or synthetic oil according DIN 51524 (BIO, other on demand)
Viscosity range	10 to 220 mm ² /s
Recommended oil	ISO VG 10 to 68 cSt (conf. DIN 51 519)
Filtration	According ISO/DIN 4406 17/15/12 (NAS 1638 class 6)
Fluid temperature range	-30 to +80°C (attention to the viscosity range)
Ambient temperature range	-40 to +60°C
Speed range	100 to 1800 rev/min
Direction of rotation	Bi-directional
Suction height	max 500mm
Operation pressure on suction port	-0,2 Bar to 0,5 Bar
Max pressure on output port	500 Bar
Axial force on driving shaft	Not allowed
Radial force on driving shaft	On request
Port connections	Via fittings ISO 228/1 (BSP), other on demand)

Size 3 (Solid concept)

500 Bar

16,50 to 33,19 cm³/rev



Ordering Code:

(Example)	PW	/06	-500	33.19	/I	-F	-Sxxx
Radial piston pump Size 2	↑						
Number of pistons (see table)		↑					
Max Pressure - 500 Bar			↑				
Displacement (cm ³ /rev)				↑			
Connection for second pump - (connection to 2 nd HP-pump) (GP2 = gearpump size 2)					↑		
Seal version (Omit = NBR) - F = FPM (Viton), M (Marine Version)						↑	
Special version							↑

(More P-port connections on request)

Maximum pressures and displacements of the standard program:

Size	Housing	Nb of Pistons	Pressure (bar) / displacement (cm ³) by piston diameter							
			∅ 6 mm	∅ 8 mm	∅ 9 mm	∅ 10 mm	∅ 12 mm	∅ 16 mm	∅ 19 mm	∅ 22 mm
3	PW	4							500/16,50	500/22,15
		6							500/24,75	500/33,19



HYDROSERV - Wimmerpumps

Ninovesteenweg 212 F - B 9320 Erebodegem

Tel: +32 (0)53 71 12 12

Email : contact@wimmerpumps.com

info@hydroserv.eu